

LED TUBE T8 & T5 : RAWEE LIGHTING (Update 1/8/2016)





No.	SPECIFICATION & FEATURE OEM / SUPPLIER NAME / MODEL	T8				T5		
		LED TUBE T8 9W	LED TUBE T8 16W	LED TUBE T8 18W	LED TUBE T8 18W	LED TUBE T8 18W	LED TUBE T5 18W	LED TUBE T5 30W
1	SUPPLIER MODEL GENERAL CHARACTERISTICS	72 LEDs	168 LEDs	168 LEDs	203 LEDs	140 LEDs (END-CAP)	200 LEDs	200 LEDs
2	TUBE MADE FROM : PC / GLASS / AL+PC	AL + PC	AL + PC	AL + PC	AL + PC	AL + PC	AL + PC	AL + PC
3	COVER : MILKY / CLEAR	MILKY	MILKY	MILKY	MILKY	MILKY	MILKY	MILKY
4	LAMP HOLDER	G13	G13	G13	G13	G13	G5	G5
5	LED LIFE TIME (Hrs)	50000	50000	50000	50000	50000	50000	50000
6	LIGHT TECHNICAL CHARACTERISTICS							
7	LED CHIP BRAND	EVERLIGHT	EVERLIGHT	EVERLIGHT	EVERLIGHT	EVERLIGHT	EVERLIGHT	EVERLIGHT
8	LUMINOUS FLUX (lm)	1050	2100	2200	2400	2100	2200	3500
9	EFFICIENCY (lm/W)	115	130	122	122	115	122	115
10	BEAM ANGLE	150	150	150	150	180	150	150
11	COLOUR TEMPERATURE AVAILABLE (K)	3000K / 6500K	3000K / 6500K	3000K / 6500K	3000K / 6500K	3000K / 6500K	3000K / 6500K	3000K / 6500K
12	COLOUR RENDERING INDEX (CRI)	>80	>80	>80	>80	>80	>80	>80
13	ELECTRICAL CHARACTERISTICS							
14	WATTAGE	9W	16W	18W	18W	18W	18W	18W
15	SYSTEM VOLTAGE	85-265VAC	85-265VAC	85-265VAC	85-265VAC	85-265VAC	85-265VAC	85-265VAC
16	POWER FACTOR	> 0.995	> 0.995	> 0.995	> 0.995	> 0.995	> 0.995	> 0.995
17	TOTAL HARMONIC DISTORTION	< 7%	< 7%	< 7%	< 7%	< 5%	< 7%	< 7%
18	PRODUCT DIMENSION							
19	MAXIMUM LENGTH (mm.)	600 mm.	1200 mm.	1200 mm.	1200 mm.	1200 mm.	1200 mm.	1200 mm.
20	THAILAND MARKET							
21	Price (THB)	220 THB	300 THB	350 THB	400 THB	250 THB	350 THB	450 THB
22	- 100 PCS			340 THB	390 THB			
23	- 500 PCS			*280THB	*300THB	*200 THB		
24	- 1000 PCS							
25	WARRANTY (Years)	3 Years	3 Years	3 Years	3 Years	2 Years	3 Years	3 Years
26	REMARK					MOQ: 100 PCS		

**** ผลิตภัณฑ์สินค้าดำเนินการผลิตภายในประเทศไทย ****

เครื่องหมายรับประกันคุณภาพ



LED STREET LIGHT : RAWEE LIGHTING (Update 1/8/2016)

No.	SPECIFICATION & FEATURE OEM / SUPPLIER NAME / MODEL	A SERIES			
		FLOOD LIGHT 60W / 48 LEDs	FLOOD LIGHT 100W / 72 LEDs	FLOOD LIGHT 150W / 96 LEDs	FLOOD LIGHT 300W / 168 LEDs
1	SUPPLIER MODEL GENERAL CHARACTERISTICS				
2	H/S MADE FROM :	ALUMINUM	ALUMINUM	ALUMINUM	ALUMINUM
3	REFLECTOR : CLEAR / GLASS	CLEAR	CLEAR	CLEAR	CLEAR
4	H/S HOLDER				
5	LED LIFE TIME (Hrs)	50000	50000	50000	50000
	LIGHT TECHNICAL CHARACTERISTICS				
6	LED CHIP BRAND	SAMSUNG	SAMSUNG	SAMSUNG	SAMSUNG
7	LUMINOUS FLUX (lm)	7200	12000	19000	34500
8	EFFICIENCY (lm/W)	120	120	120	120
9	BEAM ANGLE	120	120	120	120
10	COLOUR TEMPERATURE AVAILABLE (K)	3000K / 5700K	3000K / 5700K	3000K / 5700K	3000K / 5700K
11	COLOUR RENDERING INDEX (CRI)	>75	>75	>75	>75
	ELECTRICAL CHARACTERISTICS				
12	WATTAGE	60W	100W	150W	300W
13	SYSTEM VOLTAGE	85-265VAC	85-265VAC	85-265VAC	85-265VAC
14	POWER FACTOR	> 0.95	> 0.95	> 0.95	> 0.95
15	TOTAL HARMONIC DISTORTION	< 10%	< 10%	< 10%	< 10%
	PRODUCT DIMENSION				
16	MAXIMUM LENGTH (mm.)				
	THAILAND MARKET				
17	Price (THB) - 20 PCS - 50 PCS	5000 THB	7000 THB	7500 THB	11000 THB
18	WARRANTY (Years)	3 Years	3 Years	3 Years	3 Years
19	REMARK	MEANWELL Driver	MEANWELL Driver	MEANWELL Driver	MEANWELL Driver

**** ผลิตภัณฑ์สินค้าดำเนินการผลิตภายในประเทศไทย ****

เครื่องหมายรับประกันคุณภาพ







No.	SPECIFICATION & FEATURE OEM / SUPPLIER NAME / MODEL	SAVING SERIES **ราคาประหยัด**		A SERIES			B SERIES			B SERIES with SAFETY GLASS					C SERIES		HIGH-MAST
		HIGHBAY (GKL) 100W / 540 LEDs	HIGHBAY (GKL) 160W / 540 LEDs	HIGHBAY (GKH) 100W / 540 LEDs	HIGHBAY (GKH) 160W / 540 LEDs	HIGHBAY (GKH) 250W / 540 LEDs	HIGHBAY (GKA) 100W / 540 LEDs	HIGHBAY (GKA) 160W / 540 LEDs	HIGHBAY (GKA) 200W / 540 LEDs	HIGHBAY (GKA) 250W / 540 LEDs	HIGHBAY (GKF) 100W / 540 LEDs	HIGHBAY (GKF) 160W / 540 LEDs	HIGHBAY (GKF) 200W / 540 LEDs	HIGHBAY (GKF) 250W / 540 LEDs	HIGHBAY (SD) 160W / 96 LEDs	HIGHBAY (SD) 200W / 144 LEDs	HIGHMAST 450W / 180 LEDs
1	SUPPLIER MODEL																
2	GENERAL CHARACTERISTICS																
3	H/S MADE FROM :	ALUMINUM CLEAR	ALUMINUM CLEAR	ALUMINUM CLEAR	ALUMINUM CLEAR	ALUMINUM CLEAR	ALUMINUM CLEAR	ALUMINUM CLEAR	ALUMINUM CLEAR	ALUMINUM CLEAR	ALUMINUM GLASS	ALUMINUM GLASS	ALUMINUM GLASS	ALUMINUM GLASS	ALUMINUM NO REFLECTOR	ALUMINUM NO REFLECTOR	ALUMINUM GLASS
4	REFLECTOR : CLEAR / GLASS																
5	H/S HOLDER																
6	LED LIFE TIME (Hrs)	50000	50000	50000	50000	50000	50000	50000	50000	50000	50000	50000	50000	50000	50000	50000	50000
7	LIGHT TECHNICAL CHARACTERISTICS																
8	LED CHIP BRAND	EVERLIGHT	EVERLIGHT	EVERLIGHT	EVERLIGHT	EVERLIGHT	EVERLIGHT	EVERLIGHT	EVERLIGHT	EVERLIGHT	EVERLIGHT	EVERLIGHT	EVERLIGHT	EVERLIGHT	SAMSUNG	SAMSUNG	SAMSUNG
9	LUMINOUS FLUX (lm)	13500	20000	13500	20000	27500	13500	20000	24000	27500	13500	20000	24000	27500	20000	22000	49500
10	EFFICIENCY (lm/W)	135	125	135	125	110	135	125	120	110	135	125	120	110	125	110	110
11	BEAM ANGLE	60 / 90 / 110	60 / 90 / 110	60 / 90 / 110	60 / 90 / 110	60 / 90 / 110	60 / 90 / 110	60 / 90 / 110	60 / 90 / 110	60 / 90 / 110	60 / 90 / 110	60 / 90 / 110	60 / 90 / 110	60 / 90 / 110	120	120	120
12	COLOUR TEMPERATURE AVAILABLE (K)	6500K	6500K	6500K	6500K	6500K	6500K	6500K	6500K	6500K	6500K	6500K	6500K	6500K	5700K	5700K	5700K
13	COLOUR RENDERING INDEX (CRI)	>80	>80	>80	>80	>80	>80	>80	>80	>80	>80	>80	>80	>80	>75	>75	>75
14	ELECTRICAL CHARACTERISTICS																
15	WATTAGE	100W	160W	100W	160W	250W	100W	160W	200W	250W	100W	160W	200W	250W	160W	200W	450W
16	SYSTEM VOLTAGE	85-265VAC	85-265VAC	85-265VAC	85-265VAC	85-265VAC	85-265VAC	85-265VAC	85-265VAC	85-265VAC	85-265VAC	85-265VAC	85-265VAC	85-265VAC	85-265VAC	85-265VAC	85-265VAC
17	POWER FACTOR	> 0.95	> 0.95	> 0.95	> 0.95	> 0.95	> 0.95	> 0.95	> 0.95	> 0.95	> 0.95	> 0.95	> 0.95	> 0.95	> 0.95	> 0.95	> 0.95
18	TOTAL HARMONIC DISTORTION	< 10%	< 10%	< 10%	< 10%	< 10%	< 10%	< 10%	< 10%	< 10%	< 10%	< 10%	< 10%	< 10%	< 10%	< 10%	< 10%
19	PRODUCT DIMENSION																
20	MAXIMUM LENGTH (mm.)	Ø238.70 x ยาว 316.5 mm	Ø270.43 x ยาว 389.5 mm	Ø270.43 x ยาว 389.5 mm	Ø270.43 x ยาว 389.5 mm	Ø270.43 x ยาว 389.5 mm	Ø238.70 x ยาว 316.5 mm	Ø270.43 x ยาว 389.5 mm	Ø270.43 x ยาว 389.5 mm	Ø270.43 x ยาว 389.5 mm	Ø238.70 x ยาว 316.5 mm	Ø270.43 x ยาว 389.5 mm	Ø270.43 x ยาว 389.5 mm	Ø270.43 x ยาว 389.5 mm	Ø270.43 x ยาว 389.5 mm	Ø270.43 x ยาว 389.5 mm	Ø485 x Ø 298 x ล 146
21	THAILAND MARKET																
22	Price (THB)	5000 THB	5500 THB	6000 THB	6500 THB	7000 THB	6500 THB	7000 THB	7500 THB	8000 THB	7500 THB	8000 THB	8500 THB	9000 THB	8500 THB	10500 THB	25000 THB
23	- 20 PCS																
24	- 50 PCS																
25	WARRANTY (Years)	2 Years	2 Years	2 Years	2 Years	2 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	5 Years	5 Years	3 Years
26	REMARK	MEANWELL Driver	MEANWELL Driver	MEANWELL Driver	MEANWELL Driver	MEANWELL Driver	MEANWELL Driver	MEANWELL Driver	MEANWELL Driver	MEANWELL Driver	MEANWELL Driver	MEANWELL Driver	MEANWELL Driver	MEANWELL Driver	MEANWELL Driver	MEANWELL Driver	MEANWELL Driver

** ผลิตภัณฑ์สินค้าสำหรับการผลิตภายในประเทศไทย **
 เครื่องหมายรับประกันคุณภาพ



LED HIGHBAY : RAWEE LIGHTING (Update 1/8/2016)








No.	SPECIFICATION & FEATURE OEM / SUPPLIER NAME / MODEL	H SERIES			
		HIGHBAY (H) 100W / 540 LEDs	HIGHBAY (H) 160W / 540 LEDs	HIGHBAY (H) 200W / 540 LEDs	HIGHBAY (H) 250W / 540 LEDs
1	SUPPLIER MODEL GENERAL CHARACTERISTICS				
2	H/S MADE FROM :	ALUMINUM	ALUMINUM	ALUMINUM	ALUMINUM
3	REFLECTOR : CLEAR / GLASS	CLEAR	CLEAR	CLEAR	CLEAR
4	H/S HOLDER				
5	LED LIFE TIME (Hrs)	50000	50000	50000	50000
	LIGHT TECHNICAL CHARACTERISTICS				
6	LED CHIP BRAND	EVERLIGHT	EVERLIGHT	EVERLIGHT	EVERLIGHT
7	LUMINOUS FLUX (lm)	13500	20000	24000	27500
8	EFFICIENCY (lm/W)	135	125	120	110
9	BEAM ANGLE	60 / 90 / 110	60 / 90 / 110	60 / 90 / 110	60 / 90 / 110
10	COLOUR TEMPERATURE AVAILABLE (K)	6500K	6500K	6500K	6500K
11	COLOUR RENDERING INDEX (CRI)	>80	>80	>80	>80
	ELECTRICAL CHARACTERISTICS				
12	WATTAGE	100W	160W	200W	250W
13	SYSTEM VOLTAGE	85-265VAC	85-265VAC	85-265VAC	85-265VAC
14	POWER FACTOR	> 0.95	> 0.95	> 0.95	> 0.95
15	TOTAL HARMONIC DISTORTION	< 10%	< 10%	< 10%	< 10%
	PRODUCT DIMENSION				
16	MAXIMUM LENGTH (mm.)	∅238.70 x ยาว 316.5 mm	∅270.43 x ยาว 389.5 mm	∅270.43 x ยาว 389.5 mm	∅270.43 x ยาว 389.5 mm
	THAILAND MARKET				
17	Price (THB) - 20 PCS - 50 PCS	8500 THB	9000 THB 8500 THB 8000 THB	9500 THB 9000 THB 8500 THB	10000 THB 9500 THB 9000 THB
18	WARRANTY (Years)	3 Years	3 Years	3 Years	3 Years
19	REMARK	MEANWELL Driver	MEANWELL Driver	MEANWELL Driver	MEANWELL Driver

**** ผลิตภัณฑ์สินค้าดำเนินการผลิตภายในประเทศไทย ****

เครื่องหมายรับประกันคุณภาพ



LED STREET LIGHT : RAWEE LIGHTING (Update 1/8/2016)

No.	SPECIFICATION & FEATURE OEM / SUPPLIER NAME / MODEL	A SERIES			B SERIES			
		STREET LIGHT 30W / 24 LEDs	STREET LIGHT 50W / 24 LEDs	STREET LIGHT 90W / 96 LEDs	STREET LIGHT 150W / 96 LEDs	STREET LIGHT 75W / 48 LEDs	STREET LIGHT 100W / 72 LEDs	STREET LIGHT 150W / 96 LEDs
1	SUPPLIER MODEL GENERAL CHARACTERISTICS							
2	H/S MADE FROM :	ALUMINUM	ALUMINUM	ALUMINUM	ALUMINUM	ALUMINUM	ALUMINUM	ALUMINUM
3	REFLECTOR : CLEAR / GLASS	CLEAR	CLEAR	CLEAR	CLEAR	CLEAR	CLEAR	CLEAR
4	H/S HOLDER							
5	LED LIFE TIME (Hrs)	50000	50000	50000	50000	50000	50000	50000
6	LIGHT TECHNICAL CHARACTERISTICS							
7	LED CHIP BRAND	SAMSUNG	SAMSUNG	SAMSUNG	SAMSUNG	SAMSUNG	SAMSUNG	SAMSUNG
8	LUMINOUS FLUX (lm)	3900	6800	11700	17000	8250	11000	16500
9	EFFICIENCY (lm/W)	130	130	130	115	110	110	110
10	BEAM ANGLE	120	120	120	120	120	120	120
11	COLOUR TEMPERATURE AVAILABLE (K)	3000K / 5700K	3000K / 5700K	3000K / 5700K	3000K / 5700K	3000K / 5700K	3000K / 5700K	3000K / 5700K
10	COLOUR RENDERING INDEX (CRI)	>75	>75	>75	>75	>75	>75	>75
12	ELECTRICAL CHARACTERISTICS							
13	WATTAGE	30W	50W	90W	150W	75W	100W	150W
14	SYSTEM VOLTAGE	85-265VAC	85-265VAC	85-265VAC	85-265VAC	85-265VAC	85-265VAC	85-265VAC
15	POWER FACTOR	> 0.95	> 0.95	> 0.95	> 0.95	> 0.95	> 0.95	> 0.95
15	TOTAL HARMONIC DISTORTION	< 10%	< 10%	< 10%	< 10%	< 10%	< 10%	< 10%
16	PRODUCT DIMENSION							
16	MAXIMUM LENGTH (mm.)							
17	THAILAND MARKET							
17	Price (THB)	2500 THB	3000 THB	7000 THB	8000 THB	6000 THB	7500 THB	9000 THB
17	- 20 PCS	2300 THB	2800 THB			5500 THB	7000 THB	8500 THB
17	- 50 PCS	2000 THB	2500 THB			5000 THB	6500 THB	8000 THB
18	WARRANTY (Years)	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years
19	REMARK			MEANWELL Driver + Surge 20 KA	MEANWELL Driver + Surge 20 KA	MEANWELL Driver	MEANWELL Driver	MEANWELL Driver

**** ผลิตภัณฑ์สินค้าดำเนินการผลิตภายในประเทศไทย ****
เครื่องหมายรับประกันคุณภาพ

